

# SECURITHERM thermostatic mixer

Ref. H9642

Mixer only for mixer set with retracting hand spray





## DESCRIPTION

**SECURITHERM thermostatic mixer - Ref. H9642**

SECURITHERM thermostatic single control sequential sink mixer set with retracting hand spray.  
 Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Sequential: opens and closes with cold water.  
 No risk of cross flow between the hot and cold water.  
 No non-return valves on the inlets.  
 Scale-resistant thermostatic sequential cartridge for single control temperature and flow-rate adjustment.  
 Temperature can be adjusted from cold water to 40°C with maximum temperature limiter set at 40°C.  
 Body with smooth interior.  
 No manual contact thanks to Hygiene control lever L. 100mm.  
 Mixed water brass outlet L. 160mm.  
 PEX flexibles F3/8" and reinforced fixing via 2 stainless steel rods.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

**SECURITHERM thermostatic mixer - Ref. H9642**

Connector	F3/8"
Technology	SECURITHERM sequential Securitouch
Temperature limiter	40°C
Finish	Chrome-plated brass
Norms	 ACS 
Warranty	
Repairability	



## ADVANTAGES

-  Sequential: opens/closes with cold water
-  Hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Hygiene: transparent flexible with smooth interior

