


SECURITHERM thermostatic mixer

Ref. H9642

Mixer only for mixer set with retracting hand spray







DESCRIPTION

SECURITHERM thermostatic mixer - Ref. H9642

SECURITHERM thermostatic single control sequential sink mixer set with retracting hand spray.
 Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Sequential: opens and closes with cold water.
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Scale-resistant thermostatic sequential cartridge for single control temperature and flow-rate adjustment.
 Temperature can be adjusted from cold water to 40°C with maximum temperature limiter set at 40°C.
 Body with smooth interior.
 No manual contact thanks to Hygiene control lever L. 100mm.
 Mixed water brass outlet L. 160mm.
 PEX flexibles F3/8" and reinforced fixing via 2 stainless steel rods.
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic mixer - Ref. H9642

Connector	F3/8"
Technology	SECURITHERM sequential Securitouch
Temperature limiter	40°C
Finish	Chrome-plated brass
Norms	 ACS 
Warranty	
Repairability	

ADVANTAGES



Sequential: opens/closes with cold water



Hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Hygiene: transparent flexible with smooth interior

