

TEMPOMATIC MIX 4 electronic mixer

Ref. 493510

Recessed mains supply, stopcocks



DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 493510

Wall-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated stainless steel body L. 190mm.
Cap fixed in place by 2 concealed screws.
F3/8" stopcocks.
For wall-mounted cross wall installation.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronic unit



Anti-bacterial duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 493510

| | |
|---------------|-------------------------|
| Supply | 230/6V mains (recessed) |
| Connector | F3/8" |
| Technology | Electronic |
| Spout length | 190mm |
| Flow rate | 3 lpm |
| Norms | ACS CE SVGW |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |

