

# TEMPOMATIC MIX 4 electronic mixer

Ref. 493516

Integrated batteries






## DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493516**





Wall-mounted electronic basin mixer:  
 Battery-operated with integrated 123 6V Lithium batteries.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body L. 190mm.  
 Cap fixed in place by 2 concealed screws.  
 F3/8" stopcocks.  
 For cross wall installation.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493516**

|               |   |
|---------------|---|
| Supply        | 6V batteries  |
| Connector     | F3/8"   |
| Technology    | Electronic  |
| Spout length  | 190mm   |
| Flow rate     | 3 lpm   |
| Norms         | ACS  |
| Warranty      |      |
| Repairability |      |

## ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated electronics
-  Replace batteries without removing mixer

