

## BINOPTIC electronic tap

Ref. 388015

Mains supply







### DESCRIPTION

**BINOPTIC electronic tap - Ref. 388015**

Deck-mounted electronic basin tap:  
 Independent IP65 electronic control unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated brass body.  
 PEX flexible with filter and solenoid valve M3/8".  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Spout with smooth interior and low volume of water (reduces bacterial development).  
 Drop height: 170mm for semi-recessed washbasins.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### ADVANTAGES

-  90% water savings
-  Hygiene: no manual contact
-  LED diagnostic aids
-  Sleek design

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 388015**

Supply	Main supply 230/12 V
Connector	M3/8"
Technology	Electronic
Drop height	170mm
Spout length	175mm
Flow rate	3 lpm
Norms	   
Warranty	

