

TEMPOMATIC 4 electronic tap

Ref. 443500

Recessed mains supply



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443500





Wall-mounted electronic basin tap:
 230/6V recessed mains supply.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body L. 190mm.
 Cap fixed in place by 2 concealed screws.
 Stopcock.
 Wall-mounted fixings.
 Recessed inlet.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443500

| | |
|---------------|--------------------------------|
| Supply | 230/6V mains supply (recessed) |
| Connector | M1/2" |
| Technology | Electronic |
| Spout length | 190mm |
| Flow rate | 3lpm |
| Norms | ACS CE SVGW |
| Warranty | 30 YEARS WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated electronics
-  Anti-bacterial duty flush

