

# PREMIX NANO thermostatic mixing valve

Ref. 732230

For mixed water from 34 - 60°C





## DESCRIPTION

**PREMIX NANO thermostatic mixing valve - Ref. 732230**

Thermostatic mixing valve for mixed water distribution from 34 - 60°C:  
 For 1 to 2 taps or 1 shower.  
 Anti-scalding safety: automatic water shut-off in case of hot or cold water supply failure.  
 Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.  
 Non-return valves and filters.  
 Recommended flow rate range: 3 - 12 lpm.  
 Thermal shocks are possible.  
 Polished chrome body, hot water inlet F3/8", cold water inlet M3/8" and mixed water outlet M3/8".  
 Supplied with 3/8" connection kit.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

**PREMIX NANO thermostatic mixing valve - Ref. 732230**

|            |   |
|------------|---|
| Connector  | 3/8"  |
| Technology | Thermostatic  |
| Height     | 70mm  |
| Finish     | Chrome-plated   |
| Norms      |    |
| Warranty   |    |



## ADVANTAGES

-  Automatic shut-off if hot or cold water fails
-  Temperature stability
-  Accessible filters and non-return valves
-  Thermo-reactive cell

