

TEMPOMATIC 4 urinal valve

Ref. 479412

Electronic with integrated batteries



DESCRIPTION


TEMPOMATIC 4 urinal valve - Ref. 479412

Exposed electronic urinal valve with integrated batteries:
 Battery-operated with integrated CR 123 6V Lithium batteries.
 For wall-mounted, exposed installation.
 Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.
 Shockproof infrared presence detection sensor.
 Detection delay is 10 sec.
 3 programmes (rinsing volume adjustable in accordance to the type of urinal).
 High-frequency mode (exclusive to DELABIE):
 - short rinse after each user
 - complementary rinse after busy period.
 Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.
 Compatible with rain water.
 Flow rate 0.15 L/sec. at 3 bar, can be adjusted.
 Integrated stopcock and flow rate adjuster.
 One-piece chrome-plated metal body.
 M1/2" connection.
 Angled for recessed supply with Ø 35mm neck tube.
 For standard urinals: 50mm gap from wall.
 Suitable for people with reduced mobility.
 30-year warranty.





Ideal for replacing old installations:
 Can easily be installed where there was previously a time flow urinal.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 urinal valve - Ref. 479412

| | |
|-------------------|---|
| Supply | 6V batteries |
| Connector | M1/2" |
| Technology | Electronic |
| Height | 450mm |
| Depth | 85mm |
| Flow rate | 0.15 l/sec. |
| Width to the wall | 50mm |
| Warranty |  |

ADVANTAGES

-  Total hygiene: no manual contact
-  High-frequency mode
-  Batteries integrated into the valve body
-  Hygienic duty flush

