## SECURITHERM EP pressurebalancing basin mixer

Ref. 2564T5EP

Single hole, single control tall mixer with EP cartridge



SECURITHERM EP pressure-balancing basin mixer - Ref. 2564T5EP

Deck-mounted SECURITHERM basin mixer with pressure-balancing. Single hole, single control mixer with swivelling spout H. 205mm L. 170mm. Tall mixer with BIOSAFE hygienic outlet suitable for fitting a BIOFIL point-of-use filter.

Anti-scalding safety: HW flow reduces if CW supply fails (and vice versa). Stable temperature regardless of pressure and flow rate variations in the system.

 $\ensuremath{\text{\varnothing}}$  35mm ceramic cartridge with pressure balancing with pre-set maximum temperature limiter.

Body and spout with smooth interiors (reduces bacterial development). Thermal shocks are possible without removing the control lever or shutting off the cold water.

Flow rate regulated at 5 lpm.

Chrome-plated brass body and base.

Hygiene control lever L. 185mm requires no manual contact.

PEX flexibles F3/8" with filters and non-return valves.

Fixings reinforced via 2 stainless steel rods.

Mechanical mixer with pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility. Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2564T5EP

Technology  SECURITHERM EP mixer  Height  362mm  Drop height  205mm  Spout length  170mm  Flow rate  5 lpm  Temperature limiter  Yes  Finish  Chrome-plated brass  Norms	Connector	F3/8"
Drop height 205mm  Spout length 170mm  Flow rate 5 lpm  Temperature limiter Yes  Finish Chrome-plated brass	Technology	SECURITHERM EP mixer
Spout length 170mm  Flow rate 5 lpm  Temperature limiter Yes  Finish Chrome-plated brass	Height	362mm
Flow rate 5 lpm  Temperature limiter Yes  Finish Chrome-plated brass	Drop height	205mm
Temperature limiter Yes  Finish Chrome-plated brass	Spout length	170mm
Finish Chrome-plated brass	Flow rate	5 lpm
	Temperature limiter	Yes
Norms ACS WRAS (1)	Finish	Chrome-plated brass
<u>⊃∩</u>	Norms	ACS WRAS (1)
Warranty	Warranty	30 WARRANTY



## **ADVANTAGES**



EP: HW flow reduces if CW supply



EP: reduces pressure variations



Thermal shocks are possible without removing lever



Hygiene: smooth interior reduces bacteria

