

# SECURITHERM thermostatic shower mixer

Ref. 9741

Dual control thermostatic shower mixer



## DESCRIPTION

**SECURITHERM thermostatic shower mixer - Ref. 9741**

SECURITHERM dual control thermostatic shower mixer:  
Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold water showers if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge to adjust the temperature.

¼-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 41°C.

Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and ERGO control knobs.

M1/2" shower outlet.

Mixer with no connectors with integrated filters and non-return valves on the F3/4" inlets.




Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM thermostatic shower mixer - Ref. 9741**

Connector	M1/2"
Technology	SECURITHERM dual control thermostatic mixer, Securitouch
Length	286mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	

## ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Double maximum temperature limiter



Securitouch thermal insulation prevents burns



Mixer specifically for refurbishment

