# SECURITHERM thermostatic shower mixer

Ref. 9741

Dual control thermostatic shower mixer

## DESCRIPTION

**SECURITHERM thermostatic shower mixer - Ref. 9741**

SECURITHERM dual control thermostatic shower mixer:
Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold water showers if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge to adjust the temperature.
¼-turn ceramic head for flow rate adjustment.
Temperature control from 25 - 41°C.
Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and ERGO control knobs.
M1/2" shower outlet.
Mixer with no connectors with integrated filters and non-return valves on the F3/4" inlets.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

## ADVANTAGES

- SECURITHERM: Optimum anti-scalding safety
- Double maximum temperature limiter
- Securitouch thermal insulation prevents burns
- Mixer specifically for refurbishment

## TECHNICAL CHARACTERISTICS

**SECURITHERM thermostatic shower mixer - Ref. 9741**

| | |
|---|---|
| Connector | M1/2" |
| Technology | SECURITHERM dual control thermostatic mixer, Securitouch |
| Length | 286mm |
| Flow rate | 9 lpm |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS |
| Warranty | 30 YEAR WARRANTY |