

## SECURITHERM shower panel

Ref. 792370

Thermostatic time flow


### DESCRIPTION

**SECURITHERM shower panel - Ref. 792370**

Thermostatic time flow shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if the cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Handset with removable flexible via rapid push-fit STOP connector.  
 ~30-second time flow valve for control of sliding handset on chrome-plated rail.  
 Flow rate 6 lpm at 3 bar.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.





### TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792370**

|                     |   |
|---------------------|---|
| Connector           | M $\frac{1}{2}$ "   |
| Technology          | Time flow   |
| Height              | 1050mm  |
| Depth               | 65mm  |
| Width               | 210mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | Thermostatic  |
| Finish              | Aluminium   |
| Norms               | ACS   |
| Warranty            |  |



### ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off iff cold water fails
-  80% water savings
-  Aluminium frame, brass controls

