

BIOSAFE mechanical basin mixer

Ref. 2621

Single hole mechanical mixer with no spout, H. 95mm L. 110mm







DESCRIPTION

BIOSAFE mechanical basin mixer - Ref. 2621










Deck-mounted mechanical basin mixer.
 Single hole mechanical mixer H. 95mm L. 110mm.
 No spout: hygienic flow straightener integrated into the body.
 Securitouch thermal insulation prevents burns.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
 Mixer body with smooth interior and very low water volume (limits bacterial development).
 Flow rate regulated at 4 lpm.
 Solid control lever.
 No pop-up waste.
 PEX flexibles F3/8", rotating unions.
 Fixing reinforced by two stainless steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.
 Also available with copper tails.

ADVANTAGES

-  Hygiene: body with very low water volume
-  Maximum hygiene: no spout
-  Thermal shocks are possible
-  Pre-set maximum temperature limiter

TECHNICAL CHARACTERISTICS

BIOSAFE mechanical basin mixer - Ref. 2621

Connector	F3/8"
Technology	BIOSAFE mechanical mixer
Height	180mm
Length	220mm
Drop height	95mm
Spout length	110mm
Flow rate	4 lpm
Temperature limiter	Yes
Norms	       
Warranty	
Repairability	