

## TEMPOMIX 3 time flow mixer

Ref. 794350

Soft-touch operation









### DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 794350




Wall-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation via the push-button.  
 Time flow pre-set at ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Chrome-plated metal body M $\frac{1}{2}$ ".  
 Swivelling spout L. 150mm.  
 Filters and non-return valves.  
 Adjustable maximum temperature limiter.  
 M $\frac{1}{2}$ " offset connectors for centres from 130 - 170mm.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 794350

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Length	200mm
Width	150mm
Spout length	150mm
Flow rate	3 lpm
Norms	    
Warranty	

### ADVANTAGES

-  Exceptional water savings: 85%
-  Soft-touch operation
-  Sleek and slim design

