

BLACK BINOPTIC electronic tap

Ref. 478035

Battery-operated, H. 90mm







DESCRIPTION

BLACK BINOPTIC electronic tap - Ref. 478035



Deck-mounted matte black electronic basin tap:
 Independent IP65 electronic control unit.
 123 6V Lithium battery-operated.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated brass body.
 Matte black chrome finish.
 PEX flexible with filter and solenoid valve M3/8".
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking safety.
 Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES

-  90% water savings
-  Hygiene: no manual contact
-  Anti-bacterial proliferation duty flush
-  LED diagnostic aids

TECHNICAL CHARACTERISTICS

BLACK BINOPTIC electronic tap - Ref. 478035

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Finish	Matte black chrome
Norms	ACS 
Warranty	
Repairability	