

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9768

Thermostatic mixer with no non-return valves







DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9768





SECURITHERM dual control thermostatic shower mixer. Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).
 No risk of cross flow between hot and cold water.
 Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
 Prevents cold showers: shuts off automatically if the hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic cartridge for temperature adjustment.
 ¼-turn ceramic head for flow rate adjustment.
 Temperature control up to 43°C.
 Double temperature limiter: 1st limiter set at 41°C, 2nd limiter set at 43°C.
 Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 Flow rate limited to 9 lpm at 3 bar.
 Ergonomic controls.
 M½" shower outlet.
 F¾" inlets with integrated filters.
 Mixer supplied with offset STOP/CHECK wall connectors M½" M¾".
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

ADVANTAGES

-  SECURITHERM: optimal anti-scalding safety
-  Maximum hygiene: no non-return valves
-  Securitouch thermal insulation prevents burns
-  Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9768

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer, no non-return valves
Length	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	