

## TEMPOMATIC 5 electronic tap

Ref. 449000

Mains supply - recessed unit





### DESCRIPTION

TEMPOMATIC 5 electronic tap - Ref. 449000





Deck-mounted electronic basin tap:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated metal body.  
 PEX flexible F3/8" with stopcock and filter.  
 Fixing reinforced by two stainless steel rods.  
 Anti-blocking security.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic tap - Ref. 449000

Supply	230/6V mains supply
Connector	F3/8"
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	 ACS
Warranty	

### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated solenoid valve
-  Recessed mains supply

