

## TEMPOMATIC 5 electronic tap

Ref. 449101

Mains - plug-in








### DESCRIPTION

TEMPOMATIC 5 electronic tap - Ref. 449101

Deck-mounted electronic basin tap:  
 230/6V recessed mains supply via plug.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated metal body.  
 PEX flexibles F3/8" with filter.  
 Fixing reinforced by two stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic tap - Ref. 449101

|              |   |
|--------------|---|
| Supply       | 230/6V mains supply   |
| Connector    | F3/8"   |
| Technology   | Electronic  |
| Drop height  | 74mm  |
| Spout length | 105mm   |
| Flow rate    | 3 lpm   |
| Finish       | Chrome-plated metal   |
| Norms        |     |
| Warranty     |    |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Mains supply via plug

