

TEMPOMATIC MIX 5 electronic basin mixer

Ref. 499100

Mains supply - recessed unit





DESCRIPTION

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499100

Deck-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499100

| | |
|--------------|--|
| Supply | 230/6V mains supply |
| Connector | F3/8" |
| Technology | Electronic |
| Drop height | 74mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Finish | Chrome-plated metal |
| Norms |  ACS |
| Warranty |  30 YEAR WARRANTY |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve

