

Recessed waterproof housing for BINOPTIC

Ref. 370PBOX

Batteries, kit 1/2



DESCRIPTION

Recessed waterproof housing for BINOPTIC - Ref. 370PBOX


Recessed waterproof housing for BINOPTIC 2, kit 1/2:
Battery-operated with CR123 Lithium 6V batteries.

Recessed waterproof housing:

- Collar with waterproof seal.
 - Hydraulic connection from the exterior and maintenance from the front.
 - Modular installation (rails, solid walls, panels).
 - Compatible with walls from 10 to 120mm (whilst maintaining the minimum recessing depth of 83mm).
 - Adaptable standard pipework or "pipe in pipe".
 - Integrated stopcock and flow rate adjuster, filter and solenoid valve are accessible from the front.
 - BINOPTIC 2 tap F $\frac{1}{2}$ ".
 - Supplied in 2 kits: secured system purge without sensitive elements.
- 30-year warranty.
Order with control plate references: 370106 or 370116.

TECHNICAL CHARACTERISTICS

Recessed waterproof housing for BINOPTIC - Ref. 370PBOX

| | |
|-----------|---|
| Connector | F $\frac{1}{2}$ " |
| Height | 150mm |
| Depth | 83-190mm |
| Width | 175mm |
| Norms | ACS |
| Warranty |  |

ADVANTAGES



Installation recessed in wall



6V Lithium batteries



100% waterproof housing

