

# SECURITHERM time flow shower kit

Ref. 792219

Thermostatic time flow, kit 2/2



## DESCRIPTION

**SECURITHERM time flow shower kit - Ref. 792219**

Recessed thermostatic time flow shower, kit 2/2:  
 Tamperproof polished satin stainless steel plate 195 x 220mm.  
 SECURITHERM thermostatic mixer ¾".  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate set at 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Concealed fixings, M½" stopcocks.  
 Integrated non-return valves and filters.  
 Chrome-plated Bayblend® control knob.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 Order with waterproof housing ref. 792BOX.

## ADVANTAGES



Thermostatic temperature control





Instant shut-off if cold water fails



80% water savings

## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower kit - Ref. 792219**

Connector	½"
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	6 lpm
Finish	Satin finish stainless steel
Norms	ACS  
Warranty	