

SECURITHERM time flow shower mixer

Ref. 792218

Thermostatic time flow, kit 2/2








DESCRIPTION

SECURITHERM time flow shower mixer - Ref. 792218





Recessed thermostatic time flow shower mixer:
 Tamperproof satin finish stainless steel control plate 195 x 220mm.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Temperature can be adjusted from 32 to 40°C, pre-set at 38°C.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate set at 9 lpm at 3 bar.
 Concealed fixings, stopcocks M $\frac{1}{2}$ ".
 Integrated non-return valves and filters.
 Chrome-plated Bayblend® control knob.
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with recessed housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower mixer - Ref. 792218

Connector	$\frac{1}{2}$ "
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	9 lpm
Finish	Satin finish stainless steel
Norms	   
Warranty	

ADVANTAGES

- 
Thermostatic temperature control
- 
Instant shut-off if cold water supply fails
- 
80% water savings
- 
System tested to over 500,000 operations

