TEMPOFIX 3 frame system for urinals

Ref. 543006D

Steel frame system for urinals with flexible 1/2"



ADVANTAGES



Easy and quick to install: supplied pre-mounted



Height and centres can be adjusted



Can be adjusted to wall thickness



Compatible with battery-operated electronic valves

DESCRIPTION

TEMPOFIX 3 frame system for urinals - Ref. 543006D

Frame system for urinal with flexible ½", kit ½:

Black powder-coated steel frame for wall-mounted installation.

Fixes to floor and load-bearing walls with anchoring bolts supplied.

Adjustable bracket from 95 - 280mm.

Frame height can be adjusted from 0 to 200mm.

Ø 50mm soil pipe with waterproof seal.

Tube with ½" brass connection for urinals with flexible inlet.

Delivered pre-mounted.

Compatible with solid wall finishes from 13 - 120mm.

Supplied with recessed housing.

Valve configured for system flush, with accessories and connection protection..


30-year warranty.


Order with control plate references 430006, 430016, 430036, 778700 or 778707.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 frame system for urinals - Ref. 543006D

Connector	1/2"
Height	985 - 1,385mm
Depth	160 - 220mm
Width	430mm
Finish	Black powder-coated steel
Warranty	30 g





© DELABIE