

Control plate for TEMPOMATIC 4 for urinals

Ref. 430000

Recessed electronic mains supply valve - For urinals



DESCRIPTION

Control plate for TEMPOMATIC 4 for urinals - Ref. 430000

TEMPOMATIC 4 electronic valve F½", kit 2/2.
230/6V mains supply.
Solenoid valve enables opening and closing of water.
Brushed stainless steel wall plate 145 x 145mm with integrated electronics.
Shock-resistant infrared presence detection sensor.
Detection delay is 10 seconds.
3 programmes (rinsing volume can be adjusted according to urinal type).
High frequency mode (exclusive to DELABIE).
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vaccums.
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.
TEMPOMATIC 4 F½" valve compatible with sea water, rain water and grey water.
Installation in waterproof housing with waterproof collar, transformer, filter and stopcock.
Suitable for people with reduced mobility.
30-year warranty.
Order with frame system references 543000 for urinals Ø 35mm, 543000D for urinals with flexible ½" or with recessed housing 430SBOX.

ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high-frequency mode








Hygienic duty flush



Compatible with mains supply

TECHNICAL CHARACTERISTICS

Control plate for TEMPOMATIC 4 for urinals - Ref. 430000

Supply	230/6V mains supply
Technology	Electronic
Length	145mm
Width	145mm
Finish	Brushed stainless steel
Norms	     
Warranty	