Control plate for TEMPOMATIC 4 for urinals

Ref. 430006

Recessed electronic battery-operated valve - For urinals



DESCRIPTION

Control plate for TEMPOMATIC 4 for urinals - Ref. 430006

TEMPOMATIC 4 electronic valve F½", kit 2/2.

Battery-operated with CR 123 Lithium 6V batteries.

Solenoid valve enables opening and closing of water.

Satin finish stainless steel wall plate 145 x 145mm with integrated electronics.

Shock-resistant infrared presence detection sensor.

Detection delay is 10 seconds.

3 programmes (rinsing volume can be adjusted according to urinal type).

High frequency mode (exclusive to DELABIE):

- Short rinse after each user.
- Additional rinse after the period of increased frequency of use.

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vaccums.

Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.

TEMPOMATIC 4 $F\frac{1}{2}$ " valve compatible with sea water, rain water and grey water.

Installation in waterproof housing with waterproof collar, transformer, filter and stopcock.

Suitable for people with reduced mobility.

30-year warranty.

Order with frame system references 543006 for urinals Ø 35mm, 543006D for urinals with flexible $\frac{1}{2}$ " or with recessed housing 430PBOX.

TECHNICAL CHARACTERISTICS

Control plate for TEMPOMATIC 4 for urinals - Ref. 430006

Supply	6V batteries
Technology	Electronic
Length	145mm
Width	145mm
Finish	Satin stainless steel
Norms	CE WRAS W O O
Warranty	30 g

ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and highfrequency mode



Hygienic duty flush



123 Lithium 6V batteries

