

TEMPOFLUX control plate for urinals

Ref. 778700

Time flow valve 3 sec with soft-touch operation - For urinals



DESCRIPTION

TEMPOFLUX control plate for urinals - Ref. 778700

Control plate and time flow valve TEMPOFLUX F½", kit 2/2:

Satin finish stainless steel wall plate 145 x 145mm.

Chrome-plated metal button.

Soft-touch operation.

Time flow pre-set at ~3 seconds.

Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.

Compatible with sea water, rain water and grey water.

Complies with European standard EN 12541 (class II acoustic level).

Install in waterproof housing with waterproof collar, filter and stopcock.



Suitable for people with reduced mobility.

30-year warranty.

Order with frame system references 543006 for urinals Ø 35mm, 543006D for urinals with flexible ½" or with 778BOX recessed housing.

TECHNICAL CHARACTERISTICS

TEMPOFLUX control plate for urinals - Ref. 778700

Technology	Time flow
Length	145mm
Width	145mm
Finish	Satin stainless steel
Norms	
Warranty	

ADVANTAGES



Soft-touch operation



ECO time flow 3 seconds



Maintenance, behind plate, is easy

