## **TEMPOFLUX 2 control plate** for WCs

Ref. 578230

Soft-touch operation time flow valve, 3L/6L dual flush



## **DESCRIPTION**

TEMPOFLUX 2 control plate for WCs - Ref. 578230

Control plate for TEMPOFLUX 2 time flow direct flush, kit 2/2: Flush system without cistern, directly connected to pipework. Ø 195mm chrome-plated metal wall plate.

Concealed mechanical fixing of the wall plate.

3L/6L dual flush can be adjusted to 2L/4L.

Soft-touch operation.

For walls 70 - 130mm.

Upstream supply pipes: minimum  $\emptyset$  20mm required at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure. Complies with European standard EN 12541 class II.

30-year warranty.

Order with frame system references 578305DE.

## **ADVANTAGES**



Soft-touch operation



Direct flush: no water stagnation



Flush is instantly available




3L/6L dual flush, can be adjusted to

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 control plate for WCs - Ref. 578230

Connector	3/4"
Technology	Time flow
Depth	Walls from 70 to 130mm
Flow rate	3L/6L or 2L/4L
Diameter	Ø 195mm
Finish	Chrome-plated metal
Warranty	30 g
	30 g



© DELABIE https://www.delabie.com