# DELABIE

# Wall-mounted sequential mechanical basin mixer

Ref. 2640P

Sequential mechanical mixer with swivelling/fixed spout L. 120mm

### DESCRIPTION

#### Wall-mounted sequential mechanical basin mixer - Ref. 2640P

Wall-mounted sequential mechanical basin mixer.

Sequential mechanical mixer: opens and closes with cold water, with  $70^{\circ}$  lever turning range.

Wall-mounted mixer with swivelling under spout L. 120mm with hygienic BIOSAFE outlet.

Spout suitable for fitting a BIOFIL point-of-use filters.

Spout can be easily fixed in place.

Securitouch thermal insulation prevents burns.

Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter. Body and spout with narrow tubes with smooth interiors and very low water volume.

The speed of the water in these narrow tubes reduces biofilm development considerably.

Thermal shocks are possible without removing the control lever or shutting off the cold water supply.

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene Lever L. 150mm requires no manual contact.

Mixer with 150mm centres supplied with in-line STOP/CHECK wall connectors M1/2" M3/4" for hospitals.

Recommended installation height: 110 - 200mm above the basin surface. Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility. 30-year warranty.

## **TECHNICAL CHARACTERISTICS**

Wall-mounted sequential mechanical basin mixer - Ref. 2640P	
Supply	M1/2"
Technology	BIOSAFE sequential mechanical mixer
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	JWRAS
Warranty	30 MARCANTY



## ADVANTAGES



Sequential: opens/closes with cold water




Thermal shocks are possible without removing lever




Maximum hygiene: prevents biofilm



Spout can swivel or be fixed





# DELABIE

Repairability

