## **BIOFIL 2-month shower filter**


Ref. 30261

Non-sterile

DESCRIPTION

BIOFIL 2-month shower filter - Ref. 30261

## Anti-Legionella and all-germ



Quick to install without tools

BIOFIL anti-Legionella and all-germ shower filter. Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: $0.1 \mu m$ nominal and $0.2 \mu m$ absolute sterilising grade.
Qualified water volume per duration of use: 6,000 litres.
Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter
only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours
(cumulative total).
Non-sterile filter.
CE Class I medical device.
Weight: empty filter 105g / filled filter 186g.
Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

## TECHNICAL CHARACTERISTICS

BIOFIL 2-month shower filter - Ref. 30261		
Connector	M1/2"	
Technology	Point-of-use filtration	
Height	62mm	
Length	194mm	
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar	
Diameter	56mm	
Lifespan	2 months	
Norms	ACS WRAS BWGL CE	

