

# BIOFIL 4-month tap and wall shower filter

Ref. 30451

Non-sterile



## DESCRIPTION

### BIOFIL 4-month tap and wall shower filter - Ref. 30451

BIOFIL anti-Legionella and all-germ tap and wall shower filter, laminar flow. Device made from ABS. Membrane type: tubular microfiltration. Membrane made from polyethylene. Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade. Qualified water volume per duration of use: 12,000 litres. Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap). Space saving, suitable for taps with a low spout height: H. 63mm, Ø 56mm. Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste). Maximum upstream pressure at the point-of-use: 5 bar. Maximum lifespan: 4 months after installation. Resistance to thermal shocks: 70°C for 30 minutes. Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total). Non-sterile filter. CE Class I medical device . Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

## TECHNICAL CHARACTERISTICS

### BIOFIL 4-month tap and wall shower filter - Ref. 30451

Technology	Point-of-use filtration
Height	63mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56mm
Lifespan	4 months
Norms	ACS JWRAS CE KTW BWGL

## ADVANTAGES

-  Anti-Legionella and all-germ
-  Space saving
-  Optimised position: angled connection
-  Lifespan: 4 months after installation

