

## TEMPOFLUX 3 AB flush kit

Ref. 763266

Anti-blocking direct flush WC kit




### DESCRIPTION

TEMPOFLUX 3 AB flush kit - Ref. 763266

Flush system without cistern: directly connected to pipework.  
 For walls  $\leq 200\text{mm}$ .  
 Soft-touch operation.  
 AB anti-blocking system: flush only takes place once the push-button is released.  
 Time flow  $\sim 7$  seconds.  
 Vacuum breaker.  
 Stopcock and volume/flow rate adjustment, activation unit and cartridge are all integrated and accessible via the service duct.  
 Chrome-plated metal push-button.  
 Shock-resistant mechanism.  
 In-line inlet  $M\frac{3}{4}$ ".  
 Complies with European standard EN 12541 (class II acoustic level).  
 Cut-to-size threaded rod.  
 Upstream supply pipes: minimum  $\varnothing 20\text{mm}$  required at all points (including connectors).  
 Base flow rate:  $1\text{L/sec}$  at  $1\text{ bar}$  dynamic pressure.  
 With  $\varnothing 32\text{mm}$  PVC flush tube.  
 Compatible with rain water.  
 Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 AB flush kit - Ref. 763266

Connector	$\frac{3}{4}$ "
Technology	Time flow
Warranty	

### ADVANTAGES



Anti-blocking system



Cross wall installation



Flush is powerful and instantly available



Direct flush: limits the risk of leaks

