

## Self-supporting fire retardant TEMPOFIX 3 frame system for WCs

Ref. 565065

For TEMPOFLUX 3

### DESCRIPTION



Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

Self-supporting frame system for wall hung WCs, kit 1/2  
Fire retardant CF 60 min - EI60.

- Black powder-coated steel frame with large feet for load-bearing floors:
  - Frame height can be adjusted from 0 - 200mm (with 1m mark).
  - Ø 32mm flush tube with Ø 55mm connection washer and intumescent collar for fire protection.
  - ABS soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions and intumescent collar for fire protection.
  - Compatible with solid walls from 53 to 105mm (4 BA13 and tiles minimum).
  - Recessed waterproof housing with intumescent collar and fire protection set:
  - Backflow prevention device inside the housing.
  - Integrated stopcock and flow rate regulation.
- Supplied pre-mounted.  
30-year warranty.  
Order with control plate reference 763000.

### TECHNICAL CHARACTERISTICS

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

Connector	F3/4"
Technology	Time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Finish	Black powder-coated steel
Norms	
Warranty	



### ADVANTAGES



Fire retardant 60 minutes



Quick and easy to install: delivered pre-mounted



Space saving



Adapt to wall thickness

