

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs

Ref. 565065

For TEMPOFLUX 3

DESCRIPTION

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

Self-supporting frame system for wall hung WCs, kit 1/2
Fire retardant CF 60 min - EI60.

Black powder-coated steel frame with large feet for load-bearing floors:

- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer and intumescent collar for fire protection.
- ABS soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions and intumescent collar for fire protection.
- Compatible with solid walls from 53 to 105mm (4 BA13 and tiles minimum).
- Recessed waterproof housing with intumescent collar and fire protection set:
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate regulation.



Supplied pre-mounted.

30-year warranty.

Order with control plate reference 763000.

TECHNICAL CHARACTERISTICS

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

| | |
|------------|---|
| Connector | F3/4" |
| Technology | Time flow |
| Height | 1000 to 1320mm |
| Depth | 157 - 177mm |
| Width | 350mm |
| Finish | Black powder-coated steel |
| Norms |  |
| Warranty |  |



ADVANTAGES



Fire retardant 60 minutes



Quick and easy to install: delivered pre-mounted



Space saving



Adapt to wall thickness

