

## TEMPOMIX 3 AB time flow mixer

Ref. 794100AB

Soft-touch operation, AB system






### DESCRIPTION

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB





Deck-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation on the push-button.  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Tamperproof scale-resistant flow straightener.  
 Chrome-plated solid brass body.  
 PEX flexibles F3/8" with filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Adjustable maximum temperature limiter.  
 AB anti-blocking system: water will flow only when the push-button is released.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB

Connector	F3/8"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	  ACS
Warranty	

### ADVANTAGES

-  Exceptional water savings: 85%
-  Anti-blocking system
-  Soft-touch operation
-  Sleek design

