

## BINOPTIC 2 electronic tap

Ref. 373100

Mains, deck-mounted, H. 100mm




### DESCRIPTION

#### BINOPTIC 2 electronic tap - Ref. 373100

Deck-mounted satin electronic basin tap:  
 230/6V mains supply.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant aerator.  
 Adjustable duty flush (~60 seconds every 24 hours after the last use).  
 Stainless steel tap, 100mm high for inset basins.  
 Presence detection, sensor at the end of the spout optimises detection.  
 PEX flexible with filter.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Smooth interior spout with low water volume (limits bacterial niches).  
 Set detection distance, duty flush and launch thermal shocks manually.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

#### BINOPTIC 2 electronic tap - Ref. 373100

|             |   |
|-------------|---|
| Supply      | 230/6V mains supply   |
| Connector   | M3/8"   |
| Technology  | Electronic  |
| Drop height | 100mm   |
| Flow rate   | 3 lpm   |
| Finish      | Satin   |
| Norms       | ACS   |
| Warranty    |  |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

