

## BINOPTIC 2 electronic tap

Ref. 374110

Mains, deck-mounted, H. 170mm




### DESCRIPTION

#### BINOPTIC 2 electronic tap - Ref. 374110





Deck-mounted satin electronic basin tap:  
 230/6V mains supply.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant aerator.  
 Adjustable duty flush (~60 seconds every 24 hours after the last use).  
 Stainless steel tap, 170mm high for semi-recessed basins.  
 Sensor at the end of the spout optimises detection.  
 PEX flexible with filter.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Spout with smooth interior and low water volume (reduces niches where bacteria can develop).  
 Set presence detection range, duty flush and launch thermal shocks manually.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

#### BINOPTIC 2 electronic tap - Ref. 374110

|             |   |
|-------------|---|
| Supply      | 230/6V mains supply   |
| Connector   | M3/8"   |
| Technology  | Electronic  |
| Drop height | 170mm   |
| Flow rate   | 3 lpm   |
| Finish      | Chrome-plated   |
| Norms       | ACS   |
| Warranty    |  |

### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Anti-bacterial proliferation duty flush
-  LED diagnostic aids

