## **BINOPTIC 2 electronic tap**

Ref. 37403615

Batteries, deck-mounted, stopcock, H. 170mm



## **DESCRIPTION**

BINOPTIC 2 electronic tap - Ref. 37403615

Deck-mounted chrome-plated matte black electronic basin tap: Operated by CR123 Lithium 6V batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use).

Stainless steel tap, 170mm high for semi-recessed basins.

Sensor at the end of the spout optimises presence detection.

PEX flexible with stopcock, filter and Ø 15mm conical inlet.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth interior spout with low water volume (limits bacterial niches).

Set presence detection range, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush




Sleek design

## **TECHNICAL CHARACTERISTICS**

BINOPTIC 2 electronic tap - Ref. 37403615

Supply	6V batteries
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Warranty	30 g



© DELABIE https://www.delabie.com