

## BINOPTIC 2 electronic tap

Ref. 37501015

Mains, deck-mounted, stopcock, H. 250mm


### DESCRIPTION

**BINOPTIC 2 electronic tap - Ref. 37501015**

Deck-mounted chrome-plated electronic basin tap:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel tap, 250mm high for countertop basins.  
Presence detection sensor at the end of the spout optimises detection.  
PEX flexible with stopcock, filter and Ø 15mm conical inlet.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth spout interior with low water volume (reduces bacterial development).  
Set detection distance, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.





### TECHNICAL CHARACTERISTICS

**BINOPTIC 2 electronic tap - Ref. 37501015**

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	250mm
Flow rate	3 lpm
Finish	Chrome-plated
Warranty	



### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Anti-bacterial proliferation duty flush
-  LED diagnostic aids

