

## TEMPOMIX 3 time flow basin mixer

Ref. 794110

Soft-touch operation, deck mounted, H170mm




### DESCRIPTION

TEMPOMIX 3 time flow basin mixer - Ref. 794110

Deck-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation on the push-button.  
 Time flow pre-set at ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Tamperproof scale-resistant flow straightener.  
 Chrome-plated stainless steel body, H170mm for semi-recessed basins.  
 F3/8" PEX flexibles with filters and non-return valves.  
 Fixing reinforced by a back-nut.  
 Adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow basin mixer - Ref. 794110

Connector	F3/8"
Technology	Time flow
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome
Norms	  ACS
Warranty	



### ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Reinforced fixings with back-nut



Sleek design

