TEMPOMATIC 5 electronic basin tap

Ref. 449416

Batteries, cross wall



DESCRIPTION

TEMPOMATIC 5 electronic basin tap - Ref. 449416

Wall mounted electronic basin tap:

Operated by CR123 6V Lithium batteries.

Reduced stagnation solenoid valve and electronics integrated into the body of tap.

Flow rate pre-set at 3 lpm, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body, L. 150mm.

Cross wall installation for wall mounting.

Anti-blocking security.

Side temperature control with standard lever and adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Battery operated

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 449416

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	150mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Warranty	30 g

