

TEMPOMATIC 4 electronic shower valve

Ref. 443218

Battery 6V - kit 2/2




DESCRIPTION

TEMPOMATIC 4 electronic shower valve - Ref. 443218




Recessed electronic shower valve, kit 2/2:
 Tamperproof chrome-plated metal control plate Ø 149mm.
 TEMPOMATIC 4 electronic valve M1/2" for mixed water supply.
 Battery-operated with CR123 6V Lithium batteries.
 Infrared presence detection sensor. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 16 lpm at 3 bar.
 Install in waterproof housing with waterproof collar, filter and stopcock.
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with recessed waterproof housing ref. 443PBOX.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic shower valve - Ref. 443218

| | |
|------------|-------------------------------------------------------------------------------------|
| Supply | 6V batteries |
| Technology | Electronic |
| Flow rate | 16 lpm |
| Diameter | Ø 149mm |
| Finish | Chrome |
| Norms | ACS |
| Warranty |  |

ADVANTAGES

-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush
-  Sleek design

