

TEMPOMATIC Connect control plate for WC

Ref. 465000

Connect recessed electronic mains supply valve - For WCs



DESCRIPTION





TEMPOMATIC Connect control plate for WC - Ref. 465000

TEMPOMATIC Connect recessed electronic valve for direct flush, kit 2/2: Flush system without cistern: directly connected to pipework. 230/6V mains supply (cable and transformer supplied). Satin finish stainless steel wall plate 186 x 186mm. Mechanical fixing of the control plates. TEMPOMATIC F $\frac{3}{4}$ " flush valve is compatible with sea water, rain water and grey water. Improved presence detection range via a dual sensor (telemetric and infrared). Detection delay is 10 seconds. Two modes of activation:

- contactless by passing the hand in front of sensor,
- an automatic flush is activated after each user leaves.

"Intelligent" automatic rinsing: flush volume adapts according to use - 3L "short" usage, 6L "long" usage - (can be adjusted). Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use or at a pre-set time. Bluetooth® technology connects to the DELABIE Connect app or presence detection distance can be automatically adjusted via a concealed button. Supply diameter: minimum Ø 20mm interior at all points (including connectors). Base flow rate: 1L/sec at 1 bar dynamic pressure. Suitable for rimless WC pans and suitable for people with reduced mobility. 30-year warranty. Order with frame system references 564000 or 564005, or with recessed housing 464SBOX.

ADVANTAGES

-  Total hygiene: no manual contact
-  Direct flush: no water stagnation
-  Voluntary or automatic activation
-  Easy to configure & monitor operation

TECHNICAL CHARACTERISTICS

TEMPOMATIC Connect control plate for WC - Ref. 465000

Supply	230/6V Mains supply
Connector	F3/4"
Technology	Automatic
Length	186mm
Width	186mm
Finish	Satin stainless steel
Warranty	

