

# TEMPOMATIC Connect control plate for WC

Ref. 465000

Connect recessed electronic mains supply valve - For WCs



## DESCRIPTION

**TEMPOMATIC Connect control plate for WC - Ref. 465000**

TEMPOMATIC Connect recessed electronic valve for direct flush, kit 2/2: Flush system without cistern: directly connected to pipework.

230/6V mains supply (cable and transformer supplied).

Satin finish stainless steel wall plate 186 x 186mm.

Mechanical fixing of the control plates.

TEMPOMATIC F $\frac{3}{4}$ " flush valve is compatible with sea water, rain water and grey water.

Improved presence detection range via a dual sensor (telemetric and infrared).

Detection delay is 10 seconds.

Two modes of activation:

- contactless by passing the hand in front of sensor,

- an automatic flush is activated after each user leaves.

"Intelligent" automatic rinsing: flush volume adapts according to use - 3L

"short" usage, 6L "long" usage - (can be adjusted).

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use or at a pre-set time.

Bluetooth® technology connects to the DELABIE Connect app or presence detection distance can be automatically adjusted via a concealed button.

Supply diameter: minimum Ø 20mm interior at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure.

Suitable for rimless WC pans and suitable for people with reduced mobility.

30-year warranty.

Order with frame system references 564000 or 564005, or with recessed housing 464SBOX.

## TECHNICAL CHARACTERISTICS

**TEMPOMATIC Connect control plate for WC - Ref. 465000**

Supply	230/6V Mains supply
Connector	F3/4"
Technology	Automatic
Length	186mm
Width	186mm
Finish	Satin stainless steel
Warranty	

## ADVANTAGES



Total hygiene: no manual contact



Direct flush: no water stagnation



Voluntary or automatic activation



Easy to configure & monitor operation

