

# TEMPOMATIC electronic basin tap

Ref. 441100

Mains supply







## DESCRIPTION

TEMPOMATIC electronic basin tap - Ref. 441100

Cross wall electronic basin tap:  
 Independent IP44 electronic control unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.  
 Escutcheon flush to the wall.  
 Shockproof infrared presence detection sensor.  
 Anti-blocking security.  
 For panels ≤ 30mm.  
 Solenoid valve M 3/8" with integrated filter.  
 Threaded rods can be cut to size.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## ADVANTAGES

-  90% water savings
-  Total hygiene: no manual contact
-  LED diagnostic aid
-  Independent IP44 electronic control unit

## TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic basin tap - Ref. 441100

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Depth	30mm
Spout length	170mm
Flow rate	3 lpm
Warranty	