

TEMPOMATIC electronic basin tap

Ref. 441100

Mains supply




DESCRIPTION

TEMPOMATIC electronic basin tap - Ref. 441100

Cross wall electronic basin tap:
 Independent IP44 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.
 Escutcheon flush to the wall.
 Shockproof infrared presence detection sensor.
 Anti-blocking security.
 For panels ≤ 30mm.
 Solenoid valve M 3/8" with integrated filter.
 Threaded rods can be cut to size.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic basin tap - Ref. 441100

| | |
|--------------|---|
| Supply | 230/12V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Depth | 30mm |
| Spout length | 170mm |
| Flow rate | 3 lpm |
| Warranty |  |

ADVANTAGES



90% water savings



Total hygiene: no manual contact



LED diagnostic aid



Independent IP44 electronic control unit

