


Recessed nanny joint for SPORTING 2 SECURITHERM

Ref. 714612

For SPORTING 2 SECURITHERM battery-operated or time flow - Kit 1/2




DESCRIPTION

Recessed nanny joint for SPORTING 2 SECURITHERM - Ref. 714612

Recessed nanny joint, kit 1/2:
 Compact nanny bracket for SPORTING 2 SECURITHERM battery-operated or time flow shower panels.
 Recessed top or bottom inlet.
 Delivered with buttons pre-mounted for pressure test.
 Fixing plate is easy to install: bayonette system to allow maintenance of the caps in situ.
 Mounted with screwdriver or pliers.
 Modular installation (plaster rails, solid walls):
 - Installation with plaster rails (with or without struts): compatible with panels between 24 and 68mm (with a minimum recessing depth of 48mm).
 - Installation with solid walls: compatible with panels between 0 and 68mm.
 Secured system purge without sensitive elements.
 Connector M1/2".
 30 year warranty.
 Order with the SPORTING 2 SECURITHERM battery-operated shower panel with recessed supply, reference 714916, or the time flow SPORTING 2 SECURITHERM shower panel with recessed supply, references 714735 or 714735AB.

TECHNICAL CHARACTERISTICS

Recessed nanny joint for SPORTING 2 SECURITHERM - Ref. 714612

Supply	CR123 6V lithium batteries (electronic version)
Connector	M1/2"
Technology	Electronic or time flow
Flow rate	6 lpm
Warranty	

ADVANTAGES



Easy to install

