

Wall-mounted sequential mechanical basin mixer

Ref. 2436

Sequential mechanical mixer with swivelling spout




DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2436





Wall-mounted sequential mechanical basin mixer.
 Sequential over 90°: opens and closes with cold water.
 Flat swivelling under-spout, L. 200mm, with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Securitouch thermal insulation prevents burns.
 Ø 35mm ceramic cartridge.
 Pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume. (reduces bacterial development).
 Flow rate regulated at 5 lpm.
 Hygiene lever L. 200mm.
 Supplied with 2 wall-mounted STOP/CHECK connectors, M1/2" M3/4".
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2436

| | |
|---------------------|-------------------------------------------------------------------------------------|
| Connector | M1/2" |
| Technology | Sequential mechanical mixer |
| Spout length | 200mm |
| Flow rate | 5 lpm |
| Temperature limiter | YES |
| Finish | Chrome-plated brass |
| Warranty |  |

ADVANTAGES

-  Sequential: opens and closes with cold water
-  Maximum hygiene: manages biofilm
-  No non-return valves
-  No manual contact: Hygiene lever

