

# Wall-mounted sequential mechanical basin mixer

Ref. 2436S

Sequential mechanical mixer with swivelling spout




## DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2436S





Sequential mechanical basin mixer.  
 Sequential over a 90° range: opens and closes with cold water.  
 Flat swivelling under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.  
 Securitouch thermal insulation prevents burns.  
 Ø 35mm ceramic cartridge.  
 Pre-set maximum temperature limiter.  
 Body and spout with smooth interiors and low water volume (reduces bacterial development).  
 Flow rate regulated at 5 lpm.  
 Hygiene lever L. 200mm.  
 Supplied with 2 wall-mounted standard connectors, M1/2" M3/4".  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2436S

Connector	M1/2"
Technology	Sequential mechanical mixer
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated brass
Warranty	

## ADVANTAGES

-  Sequential: opens and closes with cold water
-  Maximum hygiene: manages biofilm
-  No non-return valves
-  No manual contact: Hygiene lever

