

## TEMPOMIX time flow mixer

Ref. 795209

2025 UK public price excluding VAT:







### DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795209



Cross wall single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation via the push-button.  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Chrome-plated solid brass body M $\frac{3}{4}$ ".  
 Filters and non-return valves.  
 Adjustable maximum temperature limiter.  
 Tamperproof cross wall control  $\leq$  220mm.  
 Tamperproof fixed cross wall spout  $\leq$  230mm.  
 System for fixing to the wall via anti-rotating pin, back-nut and connection clamp.  
 Threaded rods can be cut-to-size.  
 Chrome-plated metal control.  
 30-year warranty.

### ADVANTAGES

-  Exceptional water savings: 85%
-  Soft-touch operation
-  Solid brass, installation behind partition
-  Temperature selection

### TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795209

Connector	M $\frac{3}{4}$ "
Technology	Time flow
Length	230mm
Spout length	75mm
Flow rate	3 lpm
Norms	ACS  
Warranty	