TEMPOMATIC urinal valve

Ref. 428200

Electronic mains supply

2025 UK public price excluding VAT:



DESCRIPTION **ADVANTAGES** TEMPOMATIC urinal valve - Ref. 428200 Cross wall electronic urinal valve: Total hygiene: no manual contact Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M¹/₂". Cross wall installation for walls \leq 225mm. Shock-resistant infrared presence detector. ECO time flow 3 seconds Detection distance, time flow and flow rate can be adjusted at installation. Order the 230/12V transformer separately. Presence detection delay is 3 seconds. Automatic pre-rinse possible. Cross wall installation Time flow 3 sec. can be adjusted from 3 - 12 seconds. Hygienic duty flush is possible every 24 hours after last use, prevents vacuums. Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted. Wall plate flush to the wall. Hygienic duty flush Threaded rods can be cut-to-size. Compatible with rain water. Suitable for people with reduced mobility.

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428200

30-year warranty.

Supply	Secteur 12V
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0.3 l/sec.
Norms	CE
Warranty	30 B NARANTY

